

FULLY VITRIFIED HOMOGENEOUS PORCELAIN

DESIGN QUALIFYING REPORT

HOMOGENEOUS SOLID - MATT COLLECTION



Size	Code	Finish	Name
600X1200	RC.001.000103.EM.OU	Matt	Solid - Brilliant White
600X1200	RC.001.000112.MA.OU	Matt	Solid - Pearl
600X1200	RC.001.000654.MA.OU	Matt	Solid - Ash
600X1200	RC.001.000451.MA.OU	Matt	Solid - Walnut
600X1200	RC.001.000227.MA.OU	Matt	Solid - Cream
600X1200	RC.001.000159.MA.OU	Matt	Solid - Smoke
600X1200	RC.001.000257.MA.OU	Matt	Solid - Sand
600X1200	RC.001.000412.MA.OU	Matt	Solid - Coral
600X1200	RC.001.000256.MA.OU	Matt	Solid - Rose
600X1200	RC.001.000614.MA.OU	Matt	Solid - Charcoal
600X1200	RC.001.000479.MA.OU	Matt	Solid - Moka Brown
600X1200	RC.001.000611.MA.OU	Matt	Solid - Anthracite

FEATURES

DIMENSION & SURFACE QUALITY

	Description of the Test	Test Method	International Specification	Royal Ceramics Value
1	Length & Width (Average)	ISO 10545.2	Set by Manufacturer	R(600X1200mm)
	Deviation in Length & Width	ISO 10545.2	± 0.3 %	±0.2mm
2	Thickness (Average)	ISO 10545.2	Set by Manufacturer	9.0mm
	Deviation in Thickness	ISO 10545.2	± 5 %	±0.3mm
3	Straightness of Sides	ISO 10545.2	± 0.5 % (Max 2 mm)	±0.8mm
4	Rectangularity	ISO 10545.2	± 0.6 % (Max 4 mm)	±1.5mm
5	Surface Flatness	ISO 10545.2	± 1.8 mm (Max)	±1.6mm
6	Surface Quality	ISO 10545.2	Min 95 %	Min 95 %

PHYSICAL PROPERTIES

7	Water Absorption by mass (Average)	ISO 10545.3	< 0.5 %	Maximum < 0.5 %
8	Modulus of Rupture	ISO 10545.4	> 35 N/mm ²	Minimum > 35 N/mm ²
9	Abrasion Resistance (Maximum)-Deep Abrasion	ISO 10545.6	Maximum 175mm ³	Maximum < 165mm ³
10	Moh's Scale Hardness	EN 101	Set by Manufacturer	7
11	Slipperiness	ISO 10545.17	Set by Manufacturer	R=10(PTV=35 average in wet)
12	Colour Resistance to light	ISO 10545.16	Resistant	Resistant

THERMAL PROPERTIES

13	Thermal Expansion	ISO 10545.8	< 90.0 X 10 ⁻⁷ °C ⁻¹	< 65.0 X10 ⁻⁷ °C ⁻¹
14	Moisture Expansion	ISO 10545.10	Nil	N/D
15	Resistance to Thermal Shock	ISO 10545.9	Min 10 Cycle	Resistant
16	Resistance to Crazeing	ISO 10545.11	Min 4 Cycle	Resistant
17	Frost Resistance	ISO 10545.12	Resistant	Resistant

CHEMICAL PROPERTIES

18	Chemical Resistance	ISO 10545.13	Resistant	Resistant
19	Resistance to Stains	ISO 10545.14	Min Class III	Class V

RANDOMNESS & DISPLAY OF TILES

20	Display of Tiles	At least 4 tiles should be properly displayed.		
----	------------------	--	--	--

APPLICATIONS

Product is a Fully Vitrified Homogeneous porcelain tile with **high scratch hardness**. It is recommended to apply in **heavy traffic areas**. Cleaning and maintenance can be done with fresh water and household chemicals.

Certifications of Conformity



ISO 9001, ISO 13006, ISO 14001, ISO 45001



Prepared by:	Eng.Production	Date:	11/11/2023
Revision No.	Manager - QA and R & D	Date of Revision:	26/07/2024