

FULLY VITRIFIED HOMOGENEOUS PORCELAIN

DESIGN QUALIFYING REPORT

HOMOGENEOUS SOLID-POLISHED COLLECTION



Size	Code	Finish	Name
600X1200	RC.001.000107.PL.OU	Polished	Solid - Ivory
600X1200	RC.001.000103.PL.OU	Polished	Solid - Brilliant White
600X1200	RC.001.000112.PL.OU	Polished	Solid - Pearl
600X1200	RC.001.000611.PL.OU	Polished	Solid - Anthracite
600X1200	RC.001.000654.PL.OU	Polished	Solid - Ash
600X1200	RC.001.000451.PL.OU	Polished	Solid - Walnut
600X1200	RC.001.000227.PL.OU	Polished	Solid - Cream
600X1200	RC.001.000159.PL.OU	Polished	Solid - Smoke
600X1200	RC.001.000257.PL.OU	Polished	Solid - Sand
600X1200	RC.001.000256.PL.OU	Polished	Solid - Rose
600X1200	RC.001.000614.PL.OU	Polished	Solid - Charcoal

FEATURES

DIMENSION & SURFACE QUALITY

	Description of the Test	Test Method	International Specification	Royal Ceramics Value
1	Length & Width (Average)	ISO 10545.2	Set by Manufacturer	R(600X1200mm)
	Deviation in Length & Width	ISO 10545.2	± 0.3 %	±0.2mm
2	Thickness (Average)	ISO 10545.2	Set by Manufacturer	9.0mm
	Deviation in Thickness	ISO 10545.2	± 5 %	±0.3mm
3	Straightness of Sides	ISO 10545.2	± 0.5 % (Max 2 mm)	±0.8mm
4	Rectangularity	ISO 10545.2	± 0.6 % (Max 4 mm)	±1.5mm
5	Surface Flatness	ISO 10545.2	± 1.8 mm (Max)	±1.6mm
6	Surface Quality	ISO 10545.2	Min 95 %	Min 95 %

PHYSICAL PROPERTIES

7	Water Absorption by mass (Average)	ISO 10545.3	< 0.5 %	Maximum < 0.5 %
8	Modulus of Rupture	ISO 10545.4	> 35 N/mm ²	Minimum > 35 N/mm ²
9	Abrasion Resistance (Maximum)-Deep Abrasion	ISO 10545.6	Maximum 175mm ³	Maximum < 165mm ³
10	Moh's Scale Hardness	EN 101	Set by Manufacture	N/A
11	Slipperiness	ISO 10545.17	Set by Manufacture	N/A
12	Colour Resistance to light	ISO 10545.16	Resistant	Resistant

THERMAL PROPERTIES

13	Thermal Expansion	ISO 10545.8	< 90.0 X 10 ⁻⁷ °C ⁻¹	< 65.0 X10 ⁻⁷ °C ⁻¹
14	Moisture Expansion	ISO 10545.10	Nil	N/D
15	Resistance to Thermal Shock	ISO 10545.9	Min 10 Cycle	Resistant
16	Resistance to Crazing	ISO 10545.11	Min 4 Cycle	N/A
17	Frost Resistance	ISO 10545.12	Resistant	N/A

CHEMICAL PROPERTIES

18	Chemical Resistance	ISO 10545.13	Resistant	Resistant
19	Resistance to Stains	ISO 10545.14	Manufacturer is to state classification	Class II

RANDOMNESS & DISPLAY OF TILES

20	Display of Tiles	At least 4 tiles should be properly displayed.		
----	------------------	--	--	--

APPLICATIONS

Product is a Fully Vitrified Homogeneous porcelain tile with **low scratch hardness**. It is recommended to apply in **low traffic areas**. Cleaning and maintenance can be done with fresh water and household chemicals.

Certifications of Conformity



ISO 9001, ISO 13006, ISO 14001, ISO 45001



Green Building
Council of Sri Lanka

Prepared by:	Eng.Production	Date:	11/11/2023
Revision No.	Manager - QA and R & D	Date of Revision:	12/11/2024