



















 GLAZED VITRIFIED TILES					
DESIGN QUALIFYING REPORT					
DIGITAL PRINTING GLAZED VITRIFIED MARBLE COLLECTION					
SIZE 800X1200	CODE & NAME	SATIN MATT COLLECTION			
FEATURES					
Smooth matt surface with more natural colour intimates natural beauty of stone. That is reproduction of ancient tiles with value added features of glazed vitrified. The tiles has been produced on flat surface giving natural colour spectrum with good hardness					
DIMENTION & SURFACE QUALITY					
		Description of the Test	Test Method	International Specification	Royal Porcelain Value
1		Length & Width (Average)	ISO 10545.2	Set by Manufacture	800 mmX1200 mm (Squared)
		Deviation in Length & Width	ISO 10545.2	± 0.6 %	Max ± 0.30%
2		Thickness (Average)	ISO 10545.2	Set by Manufacture	10.0 mm
		Deviation in Thickness	ISO 10545.2	± 10 %	Max ± 3.0 %
3		Straightness of Sides	ISO 10545.2	± 0.5 % (Max 2 mm)	0.2 % (Max) (1.0 mm)
4		Rectangularity	ISO 10545.2	± 0.6 % (Max 4 mm)	Rectified (Diagonal ±0.3mm)
5		Surface Flatness	ISO 10545.2	± 0.5 % (Max 2 mm)	0.3 % (Max) (1.8 mm)
6		Surface Quality	ISO 10545.2	Min 95 %	Min 95 %
PHYSICAL PROPERTIES					
7		Water Absorption by mass (Average)	ISO 10545.3	< 0.5 %	0.2% (Max 0.3 %)
8		Modulus of Rupture	ISO 10545.4	> 27 N/mm ²	32.0 N/mm ²
9		Abrasive Resistance (Maximum)	ISO 10545.7	Set by Manufacture	Class III (1500 revolutions)
10		Moh's Scale Hardness	EN 101	Set by Manufacture	6.0 – 6.5
11		Density	ISO 10545.3	> 2.0 g/cc	2.4 g/c
12		Colour Resistance to light	ISO 10545.16	Resistance	Resistance
THERMAL PROPERTIES					
13		Thermal Expansion	ISO 10545.8	< 90.0 X 10 ⁻⁷ °C ⁻¹	74.0 X 10 ⁻⁷ °C ⁻¹
14		Moisture Expansion	ISO 10545.10	Nil	Nil
15		Resistance to Thermal Shock	ISO 10545.9	Min 10 Cycle	Resistant
16		Resistance to Craziing	ISO 10545.11	Min 4 Cycle	Resistant
17		Frost Resistance	ISO 10545.12	Resistance	Resistant
CHEMICAL PROPERTIES					
18		Chemical Resistance	ISO 10545.13	Min Class B	Resistance
19		Resistance to Stains	ISO 10545.14	Min Class III	Class V
RANDOMNESS & DISPLAY OF THE TILES					
20		Display of Tiles	At least 2 tiles should be properly displayed to express random effect		
APPLICATIONS					
Product features are medium abrasion resistance with significant scratch hardness .Therefore it is suitable for flooring in semi traffic areas like shops, verandas etc as well as for domestic use. Also it is not suitable for wet areas since the smooth surface may be slippery.					
Prepared by:-		Manager - QA, R &D		Date	01 – February 2024
Revision No.				Date of Revision	