DESIGN QUALIFYING REPORT							
SIZE			60cm x 60cm-Rectified				
IDENTIFICATION NAME			VIBRATO – Matt				
PRODUCT CATEGORY			Fully vitrified Full Body Porcelain				
	RC.VBT.000273.VS.05 RC.VBT.000274.VS.05		Black				
			Sand				
			Almond				
			Light Grey				
		RC.VBT.000491.MA.05	Walnut				
		RC.VBT.000456.MA.05	Beige				
			White				
FEATURES							
	Descr	iption of the Test	Test Method				
1	Length & Width (A	verage)	ISO 10545.2	R(600 x600 mm) ±0.2 mm			
2	Rectangularity (Average)		ISO 10545.2	-			
3	Thickness (Average)		ISO 10545.2	9.50 ± 0.5 mm			
4	Surface Flatness (Average)						
	Centre Curvature related to the diagonal calculated from work size		ISO 10545.2	±0.4 %			
	Edge Curvature related to the corresponding work size		ISO 10545.2	±0.4 %			
	Warpage related to the work size	o the diagonal calculated from	ISO 10545.2	±0.4 %			
5	Water Absorption by mass (Average)		ISO 10545.3	less than 0.5%			
6	Modulus of Rupture (Minimum)		ISO 10545.4	35.0 N/mm²			
7	Abrasion resistance		ISO 10545-6	165mm <sup>3</sup>			
8	Surface abrasion (PEI)		ISO 10545-7	Class III			
9	Resistance to Thermal Shock		ISO 10545.9	Resistant			
10	Resistance to Crazing		ISO 10545.11	Resistant			
12	Chemical Resistance		ISO 10545.13	Resistant			
13	Resistance to Stains		ISO 10545.14	Class V			
14	Color Resistance t	o light		Resistant			
15	Moh's Scale Hardr			7			
APPLICATIONS							

Product features are full body porcelain with high **scratch hardness**. It is suitable for flooring **in medium traffic areas**. Cleaning & maintenance can be done with fresh water and household chemicals

Prepared by:	Eng. Prod.	Date	13-07-2020
Reviewed by:	Manager - QA, R &D	Date	13-07-2020
Revision No.	0	Date of Revision	0