			60cm x 60cm-Rectified	
	IDENTIFIC	CATION NAME	BRAYMER – Matt	
PRODUCT CATEGORY			Fully vitrified Full Bo	dy Porcelain
	RC.BRM.000262.VS.05 RC.BRM.000409.VS.05		Beige	
			Light Brown	
		FE	ATURES	
	Description of the Test		Test Method	
1	Length & Width (Average)		ISO 10545.2	R(600 x600 mm) ±0.2 mm
2	Rectangularity (Average)		ISO 10545.2	-
3	Thickness (Average)		ISO 10545.2	9.50 ± 0.5 mm
4	Surface Flatness (A	Average)		
	Centre Curvature related to the diagonal calculated from work size		ISO 10545.2	±0.4 %
	Edge Curvature related to the corresponding work size		ISO 10545.2	±0.4 %
	Warpage related to the diagonal calculated from the work size		ISO 10545.2	±0.4 %
5	Water Absorption by mass (Average)		ISO 10545.3	less than 0.5%
6	Modulus of Rupture (Minimum)		ISO 10545.4	35.0 N/mm²
7	Abrasion resistance		ISO 10545-6	165mm ³
8	Surface abrasion (PEI)		ISO 10545-7	Class III
9	Resistance to Thermal Shock		ISO 10545.9	Resistant
10	Resistance to Crazing		ISO 10545.11	Resistant
12	Chemical Resistan	се	ISO 10545.13	Resistant
13	Resistance to Stair	าร	ISO 10545.14	Class V
14	Color Resistance to	o light		Resistant
15	Moh's Scale Hardr	less		7
	1	APF		

Prepared by:	Eng. Prod.	Date	25-11-2017
Reviewed by:	Manager - QA, R &D	Date	25-11-2017
Revision No.	3	Date of Revision	20-01-2020