	DESIGN QUALIFYING REPORT		
Size		40cm x 40cm	
Identification Name		RUSTIC COLLECTION	
Product Category		Fully Vitrified Full Body Porcelain	
	RC.0V3.0001B9.SM.03	BEIGE	
	RC.0V3.0003C2.SM.03	LIGHT GREEN	
	RC.0V3.0004E8.SM.03	BROWN	
CODES	RC.0V3.0006C8.SM.03	BROWNISH GREEN	
CODES	RC.0V3.0006F3.SM.03	SILVER GREY	
	RC.0V3.0007F1.SM.03	GOLDEN	
	RC.0V3.0007F2.SM.03	CREAM	
	RC.0V3.0009B3.SM.03	DARK GREY	

FEATURES						
	Description of the Test	Test Method				
1	Length & Width (Average)	ISO 10545.2	H(400.6-401.8), S(399.4-400.6) & G (398.2-399.4)			
2	Rectangularity (Average)	ISO 10545.2	0.35 %(Max)			
3	Thickness (Average)	ISO 10545.2	8.3 ± 0.2 mm			
4	Surface Flatness (Average)	ISO 10545.2	-			
	Centre Curvature related to the diagonal calculated from work size	ISO 10545.2	±0.2 % (±1.2 mm)			
	Edge Curvature related to the corresponding work size	ISO 10545.2	±0.3 % (±1.2 mm)			
	Warpage related to the diagonal calculated from the work size	ISO 10545.2	±0.3 % (±1.2 mm)			
5	Water Absorption by mass (Average)	ISO 10545.3	less than 0.5%			
6	Modulus of Rupture	ISO 10545.4	35.0 N/mm²			
7	Abrasive Resistance (Maximum)	ISO 10545.7	Class III			
8	Resistance to Thermal Shock	ISO 10545.9	Resistant			
9	Resistance to Crazing	ISO 10545.11	Resistant			
10	Chemical Resistance	ISO 10545.13	Resistant			
11	Resistance to Stains	ISO 10545.14	Class V			
12	Moh's Scale Hardness		7			
13	Display of Tiles		At least 6 tiles should be properly displayed to express random effect			

APPLICATIONS

Product features are **abrasion resistance** with high **scratch hardness** .Therefore it is suitable for flooring **in heavy traffic areas** like varendas, shops and banks. Cleaning & maintenance can be done with fresh water and household chemicals

	Prepared by:	Eng. Prod.	Date	30-09-2020	
Ī	Reviewed by:	Manager - QA, R &D	Date	30-09-2020	
	Revision No.	0	Date of Revision	-	